

IMPORTANT:

To be read in conjunction with product update, Issue 4 dated 15/9/22 at:

fminsulation.com.au/insulation/3m.php

3 Science. Applied to Life.

3M[™] Fire Barrier Duct Wrap 615+

Manufactured with a man-made vitreous spun fibre, which provides low thermal transfer properties in a lightweight, low profile, easy to apply product. The insulative properties of Duct Wrap help keep heat, fire and smoke contained.

New Internal Exposure Horizontal applications approval

- Fire tested up to 2 hours to AS 1530.4
- Allows for inclusion of access doors
- Less layers of wrapping at the seal

Please see over for the summary of the new installation method.

Available in three sizes

- Small Roll (38mm x 610mm x 7.62m roll)
- Large Roll (38mm x 1219mm x 7.62m roll)
- Collar (38mm x 152mm x 7.62m roll)



New & improved installation

Improvements to our previous multi-layer installation system for internal exposure horizontal applications.



To see the detailed installation guide, current local reports and Design Specification Sheets, please visit:



Australia www.3M.com.au/fireratedduct or scan the QR code.



New Zealand www.3M.co.nz/fireratedduct or scan the QR code.

3M Australia Pty Ltd Industrial Adhesives & Tapes Division Bldg A, 1 Rivett Road, North Ryde, NSW 2113

Phone 136 136 (*Option 2*) Email 3mindustrialaucs@mmm.com Web www.3M.com.au 3M New Zealand Ltd Industrial Adhesives and Tapes Division 94 Apollo Drive, Rosedale Auckland 0632 Phone 0800 474 787 Email 3mnzitb@mmm.com Web www.3M.co.nz Reports for wall sealing details include 3M Silicone Sealant 2000+, and build-up with Fire Rated Plasterboard.

3M is a trademark of 3M Company. © 3M 2017. All rights reserved.

AV011468104