



Sprayable Adhesive

GENERAL PURPOSE AEROSOL ADHESIVE

Date: 13 August 2020

Fact Sheet No.: TDS00657

YOUR SMART ADVANTAGES

- Economical general purpose adhesive
- Quick, clean and efficient for a wide variety of applications
- Strong, flexible adhesion qualities with high grab

USES

Bostik Sprayable Adhesive is an economical product with high grab, suitable for use in a wide variety of demanding bonding applications within the thermal insulation industry.

Bostik Sprayable Adhesive can easily be used direct from the can to produce a strong flexible bond to lightweight materials such as polythene, and aluminium foil, to themselves and most rigid plastics excluding PTFE. Adhesive application is quick, clean and efficient. Bostik Sprayable Adhesive is based upon a solvented adhesive containing synthetic rubber together with modifiers. The adhesive is amber coloured and dries transparent.

PRODUCT CHARACTERISTICS

Colour	Amber, dries transparent
Form	Aerosol
Composition	Synthetic rubber/resin tackifier in a hydrocarbon/ketone solvent blend
Solids Content	Approx. 35% (by weight)
Product Code	30813406 500ml aerosols x 12
Storage/Shelf Life	Store for up to 12 months from date of manufacture when stored in original, unopened packaging under cool, dry conditions within the temperature range of +10°C to +30°C and out of direct sunlight.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	Above +10°C
Service Temperature	-20°C to +60°C
Coverage	10 – 12m ² per 500ml can, depending on application technique and substrates being bonded
Drying Times	Adhesive becomes tacky in 1 to 3 minutes and should be bonded within 10 minutes
Solvent for Cleaning Up	White spirit

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Sprayable Adhesive refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

1. Surfaces must be clean, dry and free from dust, oil, grease and any loose material.
2. Shake can well before use.
3. Surfaces to be bonded should not be less than 10°C.

APPLICATION

4. Hold the can 25cm away from the surfaces to be bonded and apply an even coat of adhesive to both surfaces. Very porous surfaces may require two coats of adhesive.

NOTE: Bostik Sprayable Adhesive can be applied either by two way dry method on non-absorbent substrates or one-way wet method to allow positioning on porous substrates.

5. Allow adhesive to become tacky (between 1 to 3 minutes), then bond the surfaces by pressing together within 10 minutes of application.

CLEANING

6. After use, invert can and facing away, briefly spray to clear nozzle.

PRECAUTIONS IN USE

Bostik Sprayable Adhesive is not recommended for bonding plasticised or solvent sensitive materials such as expanded polystyrene. Do not expose to temperatures exceeding 50°C. Do not pierce, or burn even after use. Do not spray onto a naked flame or any incandescent material.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Sprayable Adhesive, available at www.bostik.com/uk.uk.



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com